

Label Printing Solutions For Every Level of Production

L901 Industrial Colour Label Printer

Powerful in both roll-to-roll and inline applications


The L901 combines industrial design, exceptional image quality, and high production speeds with a new ability to service and maintain the printhead "on-the-fly." This makes the L901 perfect for long roll-to-roll print jobs or inline integration with label finishers, applicators, dispensers, and more.

Producing vibrant full-colour prints in high resolution, the L901's new optimised ink formula delivers improved UV and water resistance, deeper blacks, and a longer printhead life. Large print volumes are now more economical, with five high-capacity 250ml CMYKK ink cartridges delivering an ultra-low cost per label.

Key Features

- Designed for easy integration
- ✓ On-the-fly printhead servicing
- Lower cost per print
- High speed & resolution

Optimised for these inline uses:







Presse s /Finishers

Roll to Roll

Print & Apply



Increased UV and water resistance with deeper blacks, all at a new lower cost of ownership



Touchscreen Operation

Easily store files, run and pause jobs, or perform maintenance tasks through a userfriendly interface

Industrial Build Quality

Designed for all-day operation—either roll-to-roll or inline—in a production environment

Professional Print Resolution



Label Printing Solutions For Every Level of Production

L901 Specifications

Printer:

Print method:	Memjet Waterfall Printhead Technology® 11 Integrated Circuit (IC) Chips – 70,400 nozzles
Inks:	Dye-based, 250mL CMYKK (1.25L total) — Water/UV resistant formula
Print resolution:	1600 x 1600 dpi – 1600 x 800 dpi
Print speed:	6 inches (152 mm) per second – 12 inches (305 mm) per second
Print width:	8.5 inches (216 mm)
Cutter/sheeter:	Powered

Media:

Media Size:	Width: 2"-9" (50.8 mm-229 mm) Length: 1"-48" (25.4 mm-1220 mm)
Thickness:	Minimum 0.005" (0.13 mm) Maximum 0.01" (0.3 mm, including liner)
Core diameter*:	Requires 3" (76.2 mm) cardboard core
Unwind/Rewind*:	12" (305 mm) outside diameter

Media sensors:	Gap (movable), continuous, black mark
Die-cut gap:	Minimum 0.125" (3.0 mm) Maximum 0.3" (8.0 mm)
Black mark:	3 mm wide, 25.4 mm long on left
Substrates:	Compatible with a wide range of paper, polyester, polypropylene, and vinyl label stocks

^{*}with optional XL Unwind/Rewind system, shown below



Optional XL Unwind / Rewinder available. Please talk to our team for full details.